

Drywall Masonry Adhesive 100

Gyprock Drywall Masonry Adhesive 100 is a simple and convenient way to adhere plasterboard sheets to masonry and concrete walls. It is specially formulated for Western Australian conditions and to offer excellent adhesion properties with an extending 100 minute working life once mixed.

Recommended Use

Drywall Masonry Adhesive 100 is supplied as a dry powder with easy mixing and application properties. It is used for adhering plasterboard to masonry and concrete surfaces, suitable for use in bigger projects that require mixing large batches.

Important

- Drywall Masonry Adhesive 100 is not suitable for use on wet area plasterboard in tiled areas.
- Do not mix Drywall Masonry Adhesive 100 after setting or drying has commenced.
- When mixing only use clean domestic water.
- Fresh batches of cement must be kept free of previous batches, or the working life will be shortened.
- Do not add water after mix begins to thicken and harden.
- Remove paint from any surfaces where Drywall Masonry Adhesive 100 is to be applied.
- Ensure surfaces are free from oil, grease or other foreign materials before use.
- Always use clean containers and equipment

Storage

Store plaster in a dry place. Do not place bags directly on concrete floors or damp ground. Long term storage may affect the plaster setting time and finish quality.



Product Features



Superior Adhesion

Good initial grab and excellent adhesion properties



Easy Application

Easy to mix and apply



Defined Setting Time

Extended 100 minute working life



Australian Made

Licensed by Australian Made Campaign Ltd

Drywall Masonry Adhesive 100 Specifications	
Feature	Description
Colour	Off white
Coverage	20kg fixes 30m ² plasterboard
Packaging	20kg Non re-sealable bags
Shelf Life	12 months from date of manufacture
Specific Gravity	2.3-2.4
VOC Content (as specified by GBCA)	2g/L as VOC content per material by GBCA
Product Manufacture	Gyprock Drywall Masonry Adhesive 100 is manufactured by CSR Gyprock in Australia and made to stringent product specifications.



Mixing

Pour Drywall Masonry Adhesive 100 powder slowly into water and mix to a firm creamy consistency. Use the proportion of approximately 3kg of powder with 1.5 litres of water. It is ideal to let mixture sit for 5 minutes prior to use, although mixture can be used immediately. This adhesive has a working life of 80-100 minutes. Do not mix more material than can be used 80 minutes.

Application

This information applies to non-fire rated interior walls. Leveling pads should be used where irregularities in wall surface exceed 15mm. Apply 15mm diameter daubs of adhesive standing out a minimum of 15mm. Space daubs at 450mm vertically and horizontally to the wall or back of the plasterboard. Space daubs 50mm in from the ends and edges of the sheet. Position boards and use a straight edge to tamp the boards into alignment, both vertically and horizontally. Hold the boards in position until adhesive sets. Alternatively, if a 'solid wall' effect is desired, apply Gyprock Drywall Masonry Adhesive 100 over the entire board surface with a 10mm x 10mm notched trowel before positioning and aligning.

Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

Health and Safety

Refer to the Safety Data Sheet for this product which is available from www.gyprock.com.au or contact:

CSR Gyprock
Trinity 3, 39 Delhi Rd, North Ryde NSW 2113
Australia Phone: **131 744**
New Zealand Phone: **0800 277 123**

Resources

For further information on this product please visit www.gyprock.com.au or refer to the Gyprock Red Book Residential and Commercial Installation Guides. For technical support, contact:

DESIGNLINK™

PHONE: 1800 621 117

Manufactured For Life Warranty

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto www.gyprock.com.au/warranty, or contact us on **1300 306 556**.



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Panel Boards standard



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.