

Thermal insulation for ceilings and walls,  
for improved comfort all year round.



Thermal  
performance



Non-  
combustible



Up to 80%  
recycled glass



Sound  
reduction



Energy  
Saving

Bradford Gold insulation can reduce energy used for heating and cooling by up to 45% in the roof and ceiling, and up to 15% in the wall, leading to a decrease in your energy consumption and in your energy bills.\*

Choosing the right insulation is important. You need confidence that the product installed delivers on the performance that is promised. Whether building a new home or undertaking alterations or additions to existing homes, insulating walls and ceilings with Bradford Gold insulation will provide peace of mind for you and your family.

**BREATHE EASY**

Bradford is the only approved insulation partner of the National Asthma Council Australia's Sensitive Choice® program. Bradford Gold insulation is suitable for use in the homes of asthma and allergy sufferers.



\* Reference: Original authors: Max Mosher, Caitlin McGee, Contributing author: Dick Clarke, Updated: Max Mosher 2013, Dick Clarke 2020, 2020, Insulation, Your Home, Australia's guide to environmentally sustainable homes, date accessed: 09/08/2023, <<https://www.yourhome.gov.au/passive-design/insulation>>



**Bradford Gold Ceiling Batts**  
**Key Benefits**

**THERMAL COMFORT**

Enhances thermal comfort in the roof space - acts a thermal barrier to slow down temperature change inside the home.

**ACOUSTIC COMFORT**

Forms a reliable acoustic layer across ceiling joists to reduce external noise.

**FINANCIAL COMFORT**

Save on energy costs in the home.

**NON-COMBUSTIBLE**

Non-combustible glasswool for added peace of mind.



**Bradford Gold Wall Batts**  
**Key Benefits**

**THERMAL COMFORT**

Delivers optimal thermal performance in the cavity of external wall and reduce heats transfer through walls.

**ENERGY EFFICIENCY**

Improved energy efficiency for additional cost savings.

**ACOUSTIC COMFORT**

Improves acoustic performance in home by reducing airborne noise transfer between rooms.

**PEACE OF MIND**

Backed by CSR - a leading Australian building company.



**HEALTHY HOME**

Pair Bradford Ceiling Batts with Bradford Gold Perimeter Batts and Perimeter Spacers to maintain a continuous airflow pathway and reduce the risk of mould and mildew forming in the roof space.



**THE SECRET TO LOWER ITCH AND RIGID BATTs**

Bradford Gold™ wall insulation is now manufactured with our upgraded Comfort Touch™ Technology, delivering the same trusted performance homeowners know and rely on – with an even better installation experience.



## BRADFORD GOLD INSULATION RANGE

R-VALUE (m <sup>2</sup> K/W)	THICKNESS (mm)	STANDARD SIZE (mm)	PIECES PER PACK	m <sup>2</sup> PER PACK	COVERAGE (m <sup>2</sup> )	MULTI PACK
<b>BRADFORD GOLD FOR WALLS</b>						
<b>TIMBER FRAME CONSTRUCTION</b>						
R2.0	90	1160 x 430	22	11	12.2	5
R2.0	90	1160 x 580	18	12.1	13.3	6
R2.0	75	1160 x 420	12	5.8	6.5	6
R2.0	75	1160 x 570	12	7.9	8.7	6
R2.2	75	1160 x 420	6	2.9	3.3	6
R2.2	75	1160 x 570	6	4	4.4	6
R2.5	90	1160 x 420	9	4.4	4.9	6
R2.5	90	1160 x 570	9	6	6.5	6
R2.7	90	1160 x 420	5	2.4	2.7	5
R2.7	90	1160 x 570	5	3.3	3.6	5
R4.0	140	1160 x 420	5	2.4	2.7	6
R4.0	140	1160 x 570	5	3.3	3.6	6
<b>STEEL FRAME CONSTRUCTION</b>						
R2.0	90	1200 x 450	18	9.7	9.7	6
R2.0	90	1200 x 600	18	13	12.9	6
R2.0	75	1200 x 450	12	6.5	6.5	6
R2.0	75	1200 x 600	12	8.6	8.6	6
R2.5	90	1200 x 450	9	4.9	4.9	6
R2.5	90	1200 x 600	9	6.5	6.5	6
R2.7	90	1200 x 450	5	2.7	2.7	5
R2.7	90	1200 x 600	5	3.6	3.6	5
<b>BRADFORD GOLD FOR CEILINGS</b>						
R2.5	140	1160 x 430	16	8	8	7
R2.5	140	1160 x 580	16	10.8	11.4	7
R3.0	165	1160 x 430	16	8	8.6	6
R3.0	165	1160 x 580	16	10.8	11.4	6
R3.5	185	1160 x 430	16	8	8.8	5
R3.5	185	1160 x 580	10	6.7	7.1	8
R4.1	215	1160 x 430	10	5	5.4	7
R4.1	215	1160 x 580	10	6.7	7.1	7
R5.0	240	1160 x 430	8	4	4.3	6
R5.0	240	1160 x 580	8	5.4	5.7	6
R6.0	260	1160 x 430	6	3	3.2	6
R6.0	260	1160 x 580	6	4	4.3	6
R7.0	290	1160 x 430	4	2	2.2	6
R7.0	290	1160 x 580	4	2.7	2	6

## BRADFORD GOLD PERIMETER BATTS FOR CEILINGS

R-VALUE (m <sup>2</sup> K/W)	THICKNESS (mm)	LENGTH (mm)	WIDTH (mm)	PIECES PER PACK	m <sup>2</sup> PER PACK	MULTI PACK
R3.0	100	1200 (3 x 400)	430	5pc of 1200mm, 15pc of 400mm	2.58	6
R3.0	100	1200 (3 x 400)	580	5pc of 1200mm, 15pc of 400mm	3.48	6

**Product Suitability:** Always check product suitability and limitations of use prior to selection – refer to the Product Technical Statement (PTS) available online.



CSR Bradford Locked Bag 1345 North Ryde BC NSW 1670  
bradfordinsulation.com.au

For more information call 1300 850 305  
or visit [csrbradford.com.au](http://csrbradford.com.au)



CSR Bradford

